4	\sim
1	n
ı	v

Keyword Deck Drains	Section 5.8.1.1.1	Code Cross connection devices such as check valves shall be in good working order, and shall be tested as required by the AHJ.	
Deck Slip Resistance	5.8.1.2	Materials/Slip Resistance	Α
Clean and Good Repair	5.8.1.2.1	Surfaces shall be clean and in good repair.	
Risk Management	5.8.1.2.2	The finish and profile of deck surfaces shall be maintained to prevent slips and falls.	
Tripping Hazards	5.8.1.2.3	Tripping hazards shall be avoided.	
Protect	5.8.1.2.3.1	If tripping hazards are present, they shall be repaired or promptly barricaded to project patrons/employees.	
	5.8.1.3	Deck Size/Width	
	5.8.2	Diving Boards and Pactforms	
	5.8.3	Starting Blocks	
	5.8.4	Deck Slides	
	5.8.5	Lifeguard-Related	
	5.8.6	Fencing	
	5.8.7	Aquatic Venue Cle 2 ng System	
Filter/Equipment Room	5.9	Filter (Equip ont Room	
Chemical Storage	5.9.1	nemic / Storage	
Local Codes	5.9.1.1	Chek sal STORAGE shall be in compliance with local building and fire CODES.	Α
OSHA and EPA	5.9.1.2	Chemical handling shall be in compliance with OSHA d EPA regulations.	Α
MSDS	5.9.1.3	For each chemical, STORAGE, handling and use of the chemical shall be in compliance with the manufacturer's Material Data Safety Sheets (MSDS) and labels.	Α
Access Prevention	5.9.1.4	AQUATIC VENUE chemicals shall be stored to prevent access by unauthorized individuals.	A
Protected	5.9.1.5	AQUATIC VENUE chemicals shall be stored so that they are protected from getting wet.	A
No Mixing	5.9.1.6	AQUATIC VENUE chemicals shall be stored so that if the packages were to leak, no mixing of incompatible materials would occur.	Α

[&]quot;This information is distributed solely for the purpose of pre dissemination public viewing under applicable information quality guidelines. It has not been formally disseminated by the Centers for Disease Control and Prevention. It does not represent and should not be construed to represent any agency determination or policy."