

SAFE USE OF HATCHES

Avoid falls when using or working near hatches

Contractors should take the following steps before work begins:

- ▶ Use a fixed ladder to access the roof. If there is no fixed ladder, secure any extension ladder to restrict movement.
- ▶ Include handholds (grab bars) to use when transitioning from the ladder or stairway to the roof.
- ▶ Install standard guardrails, as defined by OSHA, around the open sides of roof hatches. Guardrails protect nearby workers from tripping on or falling into an open hatch.
- ▶ Install a swing gate that opens away from the ladder/hatch opening.



For more information on fall prevention and protection, visit stopconstructionfalls.com

On the job, workers should:

- ▶ Check to make sure the way is clear of debris or materials and communicate with workers above or below before using the hatch.
- ▶ Hold onto grab bars when climbing into or out of the hatch.
- ▶ Use appropriate fall protection, including a Personal Fall Arrest System (PFAS) when working at heights of 6 ft or more above a lower level.
- ▶ Hatch lids should be closed when not in use. Hatch lids should never be used to store any materials or as a seat.

PLAN. PROVIDE. TRAIN.

Three simple steps to preventing falls.

JULY 2021

Join the Campaign to Stop Construction Falls!

www.stopconstructionfalls.com



PLAN. PROVIDE. TRAIN.



NIOSH



CPWR 
THE CENTER FOR CONSTRUCTION
RESEARCH AND TRAINING

#StandDown4Safety